

Case Size

∅ DxL(mm)

μF \ WV (SV)	10 (16)	16 (20)	25 (32)	35 (44)	50 (63)	63 (79)	100 (125)	160 (200)	200 (250)	250 (300)	350 (400)
0.47							8x12	-	-	-	-
1							8x12	8x12	8x12	8x12	8x12
2.2							8x12	8x12	8x14	10x13	10x13
3.3							8x12	8x14	10x13	10x17	10x17
4.7						8x12	8x14	10x13	10x17	10x21	10x21
10					8x12	8x14	10x13	10x17	10x21	13x21	13x21
22			8x12	8x14	10x13	10x17	10x21	13x21	13x21	13x26	16x26
33		8x12	8x14	10x13	10x17	10x17	10x21	13x21	13x26	16x26	16x32
47	8x12	8x14	10x13	10x17	10x21	10x21	13x21	13x26	16x26	16x32	16x36
100	8x14	10x13	10x17	10x21	13x21	13x26	16x26	16x32	16x36	18x36	-
220	10x21	13x21	13x26	16x26	16x32	16x36	-	-	-	-	-
330	13x21	13x26	16x26	16x32	16x36	18x36	-	-	-	-	-
470	13x26	16x26	16x32	16x36	18x36	-	-	-	-	-	-
1000	16x26	16x32	16x36	18x36	-	-	-	-	-	-	-

136

Maximun Ripple Current

(mA,rms,120Hz at 125°C)

μF \ WV (SV)	10 (16)	16 (20)	25 (32)	35 (44)	50 (63)	63 (79)	100 (125)	160 (200)	200 (250)	250 (300)	350 (400)
0.47							14	-	-	-	-
1							24	30	36	41	45
2.2							31	37	43	50	55
3.3							36	41	48	53	60
4.7						38	45	52	60	68	75
10					48	55	70	82	88	92	110
22			70	82	88	93	100	128	135	160	180
33		91	100	108	122	132	158	164	172	185	200
47	92	110	130	158	164	172	185	200	215	230	245
100	145	206	250	262	277	295	310	365	400	420	-
220	330	400	470	540	587	595	-	-	-	-	-
330	410	525	631	718	900	1000	-	-	-	-	-
470	525	720	810	900	1000	-	-	-	-	-	-
1000	960	1000	1100	1200	-	-	-	-	-	-	-