

Electrical Characteristics :

10406 Series

Inductance (μ H)	Q min.	Test Freq. (MHz)	SRF (MHz) min.	RDC (Ω) max.	IDC (mA) min.
1.0 N	20	7.960	105.0	0.20	500
1.5 N	20	7.960	75.0	0.40	500
2.2 N	20	7.960	65.0	0.60	400
3.3 N	20	7.960	50.0	0.80	400
4.7 M	20	2.520	40.0	1.00	400
6.8 M	20	2.520	30.0	1.20	400
10 M	20	2.520	20.0	1.50	300
15 M	20	2.520	10.0	2.00	300
22 M	20	2.520	6.0	2.50	300
33 M	20	0.796	4.0	3.00	300
47 M	20	0.796	3.0	4.00	300
68 M	20	0.796	2.3	6.00	200
100 M	20	0.252	2.0	10.0	200
150 M	20	0.252	1.5	20.0	200
220 M	20	0.252	1.2	40.0	200
330 M	20	0.0796	1.0	80.0	100
470 M	20	0.0796	0.9	100	100
680 M	20	0.0252	0.8	150	100
1000 M/K	20	0.0252	0.7	220	100
1500 M/K	20	0.001	0.6	330	50
2200 M/K	20	0.001	0.5	400	50
3300 M/K	20	0.001	0.4	420	25
4700 M/K	20	0.001	0.3	450	25
6800 M/K	20	0.001	0.2	500	25
10000 K	20	0.001	0.15	550	25
15000 K	20	0.001	0.1	600	25
22000 K	20	0.001	0.09	600	25

10507 Series

Inductance (μ H)	Q min.	Test Freq. (KHz)	SRF (MHz) min.	RDC (Ω) max.	IDC (mA) min.
1.0 N	20	2520	25	0.20	500
1.5 N	20	2520	15	0.30	500
2.2 N	20	796	6.00	0.40	400
3.3 N	20	796	4.00	0.50	400
4.7 M	20	252	3.00	0.60	400
6.8 M	20	252	2.00	0.90	400
10 M	20	252	1.50	1.20	300
15 M	20	79.6	1.00	1.60	300
22 M	20	79.6	0.90	2.00	300
33 M	20	79.6	0.80	2.90	300
47 M	20	25.2	0.70	3.90	300
68 M	20	25.2	0.60	6.00	300
100 M	20	25.2	0.50	8.00	200
150 M	20	25.2	0.40	12.00	200
220 M	20	25.2	0.30	16.00	200
330 M/K	20	25.2	0.20	24.00	200
470 M/K	20	1.00	0.10	39.00	200
680 M/K	20	1.00	0.09	54.00	100
1000 K	20	1.00	0.08	92.00	100
1500 K	20	1.00	0.07	140.0	100
2200 K	20	1.00	0.06	162.0	100
3300K	20	1.00	0.05	170.0	100

4700 K	20	1.00	0.04	200	50
6800 K	20	1.00	0.03	300	50
10000K/J	20	1.00	0.02	400	50
15000K/J	20	1.00	0.01	500	25
22000K/J	20	1.00	0.01	600	25

10608 Series

Inductance (μ H)	Q min.	Test Freq. (KHz)	SRF (MHz) min.	RDC (Ω) max.	IDC (mA) min.
1.0 N	20	2520	25	0.20	1000
1.5 N	20	2520	15	0.30	1000
2.2 N	20	796	6.00	0.40	1000
3.3 N	20	796	5.00	0.60	500
4.7 M	20	796	4.20	0.80	500
6.8 M	20	796	3.40	1.00	500
10 M	20	796	3.00	1.20	300
15 M	20	796	2.50	1.50	300
22 M	20	252	2.20	2.00	300
33 M	20	252	1.70	3.00	300
47 M	20	252	1.40	4.00	300
68 M	20	252	0.90	6.00	300
100 M/K	20	79.6	0.75	10.0	200
150 M/K	20	79.6	0.60	12.0	200
220 M/K	20	79.6	0.50	15.0	200
330 M/K	20	79.6	0.44	20.0	200
470 M/K	20	79.6	0.36	30.0	100
680 M/K	20	79.6	0.30	40.0	100
1000 K	20	79.6	0.24	60.0	100
1500 K	20	79.6	0.16	100	100
2200 K	20	25.2	0.12	120	100
3300 K	20	25.2	0.12	150	100
4700 K	20	25.2	0.10	180	50
6800 K	20	25.2	0.09	200	50
10000K/J	20	1.00	0.08	250	25
15000K/J	20	1.00	0.07	320	25
22000K/J	20	1.00	0.06	420	25
33000K/J	20	1.00	0.05	550	25

10610 Series

Inductance (μ H)	Q min.	Test Freq. (KHz)	SRF (MHz) min.	RDC (Ω) max.	IDC (mA) min.
1.0 N	20	2520	25	0.20	1000
1.5 N	20	2520	15	0.30	1000
2.2 N	20	796	6.00	0.40	1000
3.3 N	20	796	5.00	0.60	500
4.7 M	20	796	4.20	0.80	500
6.8 M	20	796	3.40	1.00	500
10 M	20	796	3.00	1.20	300
15 M	20	796	2.50	1.50	300
22 M	20	252	2.20	2.00	300
33 M	20	252	1.70	3.00	300
47 M	20	252	1.40	4.00	300
68 M	20	252	0.90	6.00	300
100 M/K	20	79.6	0.75	10.0	200
150 M/K	20	79.6	0.60	12.0	200
220 M/K	20	79.6	0.50	15.0	200
330 M/K	20	79.6	0.44	20.0	200
470 M/K	20	79.6	0.36	30.0	100
680 M/K	20	79.6	0.30	40.0	100